



Blue Pennant Aztec Technical Data Sheet

Blue Pennant Sandstone has been tested on the Aztec Ventilated Rainscreen System to comply with BS 8298 in accordance with standard test methods for building envelopes as specified in CWCT Technical Notes 75 & 76:

Tested Size : 1194 x 444 x 30mm



- Soft body impact – 120 Nm – No damage observed. Class 1 serviceability.
- Soft body impact – 350 Nm – No damage observed. Negligible risk - safety.
- Soft body impact – 500 Nm – No damage observed. Negligible risk - safety.
- Hard body impact – 10Nm – Minor indent. Class 2 serviceability, negligible risk - safety.

Blue Pennant can be used on all floors at a maximum of 1194 x 444 (1200 x 450 grid).

Standard Grid sizes for this stone are:

1200 x 450 mm
900 x 450 mm
900 x 300 mm
600 x 300 mm
600 x 450 mm

Finishes available on this stone are:

Honed
Sandblasted

Stone Cladding Systems
November 2022

Head Office: Stone Cladding Systems, Park House, Alkington DE6 3DH
Tel: 01335361000 Website: www.scs-stone.co.uk
Bankers: Lloyds Bank, Dig Street, Ashbourne, DE6 1DY

Directors: J.J.Kennedy