



Orion White Limestone Aztec Technical Data Sheet

Orion White Limestone has been tested on the Aztec Ventilated Rainscreen System to comply with BS 8298 in accordance with standard test methods for building envelopes as specified in CWCT Technical Notes 75 & 76:



Tested Size: 894 x 444 x 30mm

- Soft body impact - 120Nm - No damage observed. Class 1 serviceability.
- Soft body impact - 350Nm - No damage observed. Negligible risk - safety.
- Soft body impact - 500Nm - No damage observed. Negligible risk - safety.
- Hard body impact – 10Nm – Surface marking Class 1, Negligible risk - safety.

Orion White Limestone can be used on all floors, including ground floor at a maximum of 894 x 444mm (900 x 450mm grid).

Standard Grid sizes for this stone are:

900 x 450 mm
900 x 300 mm
600 x 300 mm
600 x 450 mm

Finishes available on this stone are:

Honed
Sandblasted
Tooled
Leather Effect

Stone Cladding Systems Ltd
October 2023

Head Office: Stone Cladding Systems, Park House, Alkmonton, DE6 3DH
Tel: 01335361000 Website: www.scs-stone.co.uk
Bankers: Lloyds Bank, Dig Street, Ashbourne, DE6 1DY

Directors: J.J.Kennedy