



UK Whinstone Aztec Technical Data Sheet

UK Whinstone has been tested on the Aztec Ventilated Rainscreen System to comply with BS 8298 in accordance with standard test methods for building envelopes as specified in CWCT Technical Notes 75 & 76:



Tested Size 1194 x 444 x 30mm

- Soft body impact – 120 Nm – No damage observed. Class 1 Serviceability.
- Soft body impact – 350 Nm – No damage observed. Negligible risk - safety.
- Soft body impact – 500 Nm – No damage observed. Negligible risk - safety.
- Hard body impact – 10 Nm – No damage observed. Negligible risk - safety.

UK Whinstone can be used on all floors, including ground floor, at a maximum of 1194 x 444mm (1200 x 450mm grid).

*This stone can also be proven to be suitable at 1194 x 444mm (1200 x 450mm grid) at 20mm thick.

Standard Grid sizes for this stone are:

1200 x 450 mm
1200 x 300 mm
900 x 450 mm
900 x 300 mm
600 x 300 mm
600 x 450 mm

Finishes available on this stone are:

Honed
Flamed
Sandblasted
Polished

Stone Cladding Systems Ltd
February 2017

Head Office: Stone Cladding Systems, Park House, Alkmonton DE6 3DH

Tel: 01335361000

Website: www.scs-stone.co.uk

Bankers: Lloyds Bank, Dig Street, Ashbourne, DE6 1DY

Directors: J.J.Kennedy